

Package ‘lordif’

April 5, 2012

Type Package

Title Logistic Regression Differential Item Functioning using IRT

Version 0.2-2

Date 2012-4-4

Author Seung W. Choi, with contributions from Laura E. Gibbons and Paul K. Crane

Maintainer Seung W. Choi <s-choi@northwestern.edu>

Description Analysis of Differential Item Functioning (DIF) for dichotomous and polytomous items using an iterative hybrid of (ordinal) logistic regression and item response theory (IRT)

Depends R (>= 2.7.0), MASS, msm, mvtnorm, polycor, sfsmisc, ltm,Hmisc, rms

License GPL (>= 2)

LazyLoad yes

Repository CRAN

Date/Publication 2012-04-05 05:46:25

R topics documented:

lordif-package	2
Anxiety	3
calcprob	5
calctheta	6
collapse	7
equate	8
extract	9
getcutoff	10
lordif	11
montecarlo	13
permute	15

plot.lordif	16
plot.lordif.MC	17
probgrm	18
recode	19
rundif	20
runolr	21
separate	23
tcc	24

Index	26
--------------	-----------

lordif-package	<i>LOGistic Regression Differential Item Functioning using IRT</i>
----------------	--

Description

Analysis of Differential Item Functioning (DIF) for dichotomous and polytomous items using an iterative hybrid of (ordinal) logistic regression and item response theory (IRT).

Details

Package:	lordif
Type:	Package
Version:	0.2-2
Date:	2012-4-4
License:	GPL (>=2)
LazyLoad:	yes

Ordinal logistic regression (OLR) provides a flexible framework for detecting various types of DIF. Previous efforts extended the framework by substituting the matching variable based on sum scores with IRT based trait scores and by employing an iterative process of purifying the matching variable with the use of group-specific item parameters (Crane et. al., 2006). This package represents an effort to integrate both statistical and IRT procedures into a single program. A Monte Carlo simulation approach was incorporated to derive empirical threshold values for various DIF statistics and effect size measures. The two most important functions are: `lordif` and `montecarlo`.

Author(s)

Seung W. Choi, with contributions from Laura E. Gibbons and Paul K. Crane Maintainer: Seung W. Choi <s-choi@northwestern.edu>

References

Choi, S. W., Gibbons, L. E., Crane, P. K. (2011). lordif: An R Package for Detecting Differential Item Functioning Using Iterative Hybrid Ordinal Logistic Regression/Item Response Theory and Monte Carlo Simulations. *Journal of Statistical Software*, 39(8), 1-30. URL <http://www.jstatsoft.org/v39/i08/>.

Crane, P. K., Gibbons, L. E., Jolley, L., & van Belle, G. (2006). Differential item functioning analysis with ordinal logistic regression techniques: DIF detect and difwithpar. *Medical Care*, 44(11 Suppl 3), S115-S123.

See Also

[ltm](#), [rms](#)

Examples

```
##load PROMIS Anxiety sample data (n=766)
## Not run: data(Anxiety)
##age : 0=younger than 65 or 1=65 or older
##gender: 0=Male or 1=Female
##education: 0=some college or higher 1=high school or lower
##run age-related DIF on all 29 items (takes about a minute)
## Not run: age.dif <- lordif(Anxiety[paste("R",1:29,sep="")],
## Not run: Anxiety$age, control=list(iter.qN=100,GHk=61,method="SANN"))
##print output
## Not run: print(age.dif)
##print extended output
## Not run: summary(age.dif)
##generate plots for DIF items (reference group: <65)
## Not run: plot(age.dif,labels=c("Younger","Older"))
##run Monte Carlo simulations for threshold values
##this may take several minutes
## Not run: age.dif.MC<-montecarlo(age.dif,alpha=0.05,nr=100)
##print output
## Not run: print(age.dif.MC)
##print extended output
## Not run: summary(age.dif.MC)
##generate plots for Monte Carlo threshold values
## Not run: plot(age.dif.MC)
```

Anxiety

A Measure of Anxiety

Description

The data contain responses given by 766 people sampled from a general population to the PROMIS Anxiety scale (<http://www.nihpromis.org>) composed of 29 Likert-type questions with a common rating scale (1=Never, 2=Rarely, 3=Sometimes, 4=Often, and 5=Always).

Usage

```
data(Anxiety)
```

Format

A data frame with 766 observations on the following 32 variables.

age 0=younger than 65 and 1=65 and older

gender 0=Male and 1=Female

education 0=some college or higher and 1=high school or lower

R1 I felt fearful

R2 I felt frightened

R3 It scared me when I felt nervous

R4 I felt anxious

R5 I felt like I needed help for my anxiety

R6 I was concerned about my mental health

R7 I felt upset

R8 I had a racing or pounding heart

R9 I was anxious if my normal routine was disturbed

R10 I had sudden feelings of panic

R11 I was easily startled

R12 I had trouble paying attention

R13 I avoided public places or activities

R14 I felt fidgety

R15 I felt something awful would happen

R16 I felt worried

R17 I felt terrified

R18 I worried about other people's reactions to me

R19 I found it hard to focus on anything other than my anxiety

R20 My worries overwhelmed me

R21 I had twitching or trembling muscles

R22 I felt nervous

R23 I felt indecisive

R24 Many situations made me worry

R25 I had difficulty sleeping

R26 I had trouble relaxing

R27 I felt uneasy

R28 I felt tense

R29 I had difficulty calming down

Source

<http://www.nihpromis.org>

References

PROMIS Cooperative Group. Unpublished Manual for the Patient-Reported Outcomes Measurement Information System (PROMIS) Version 1.1. October, 2008: <http://www.nihpromis.org>

Examples

```
## Not run: data(Anxiety)
```

calcprob	<i>calculates item response probabilities</i>
----------	---

Description

Calculates item response probabilities over a theta grid.

Usage

```
calcprob(ipar, theta)
```

Arguments

ipar	a data frame containing the following columns: a, cb1, cb2,..., cb(maxCat)
theta	a grid of theta values, e.g., theta <- seq(-4,4,.1)

Details

Calculates an array of item response probabilities according to the graded response model (GRM: Samejima, 1969) over a grid of theta values. Two required input objects are ipar and theta. ipar is a data frame containing item parameters in the following order: a, cb1, cb2,..., cb(maxCat). Items can have different numbers of categories. The variable maxCAT is determined by the function as the maximum number of category threshold parameters across all items plus 1. theta is a vector containing a grid of theta values.

Value

Returns an array of item response probabilities of dimension, $c(nq, ni, \text{maxCAT})$, where nq is the length of the theta grid, ni is the number of items in ipar, i.e., $nrow(\text{ipar})$, and maxCAT is the maximum number of response categories across all items.

Author(s)

Seung W. Choi <s-choi@northwestern.edu>

References

Samejima, F. (1969). Estimation of latent ability using a response pattern of graded scores. Psychometrika Monograph, 17.

See Also

[probgrm](#)

Examples

```
##item.par<-read.csv(fn,head=F,col.names=c("a","cb1","cb2","cb3"))
##theta <- seq(-4,4,.1)
## Not run: calcprob(item.par,theta)
```

calctheta	<i>calculates EAP theta and associated standard error</i>
-----------	---

Description

Calculates the Expected A Posteriori (EAP) theta and the associated posterior standard deviation (PSD) as standard error estimates.

Usage

```
calctheta(ipar, resp.data, theta, prior.mean = 0, prior.sd = 1)
```

Arguments

ipar	a data frame containing the following columns: a, cb1, cb2,..., cb(maxCat)
resp.data	a data frame containing item responses
theta	a theta grid (quadrature points)
prior.mean	prior mean
prior.sd	prior standard deviation

Details

Calculates EAP theta estimates and PSD standard error estimates based on the input item parameters (ipar) and the item response data (resp.data).

Value

A list object with the components

EAP	Expected A Posteriori estimates of theta
SE	Standard Error estimates

Note

Not all item responses may be present.

Author(s)

Seung W. Choi <s-choi@northwestern.edu>

References

Bock, R. D. & Mislevy, R. J. (1982). Adaptive EAP Estimation of Ability in a Microcomputer Environment. *Applied Psychological Measurement*, 6(4), 431-444.

See Also

[calcprob](#), [probgrm](#)

Examples

```
## Not run: calctheta(ipar, resp.data)
```

collapse	<i>collapses response categories</i>
----------	--------------------------------------

Description

collapses response categories if cell frequencies are less than the specified minimum threshold (i.e., minCell) and returns a vector of recoded values.

Usage

```
collapse(resp, group, minCell)
```

Arguments

resp	a vector of item responses
group	a vector of group designations
minCell	a minimum cell frequency

Details

Collapses item response categories in resp if the two-way contingency table (resp x group) has cell frequencies less than the minimum cell count threshold specified by minCell.

Value

a numeric vector of the same length as resp with collapsed/recoded values.

Note

Item responses are expected to start from 1 not 0 (e.g., 1, 2, 3, 4, 5 and not 0, 1, 2, 3, 4). There must be at least two unique categories after collapsing/recoding.

Author(s)

Seung W. Choi <s-choi@northwestern.edu>

See Also

[recode](#)

Examples

```
r1 <- c(1,1,2,1,1,2,2,1,2,2,1,2,2,1,1,2,1,2,2,3,3,1,2,3)
gr <- c(0,0,0,1,1,0,1,1,0,0,1,0,1,1,0,1,0,1,0,1,0,1,0,1)
collapse(r1,gr,2) #minCell=2
## returns c(1,1,2,1,1,2,2,1,2,2,1,2,2,1,1,2,1,2,2,2,2,1,2,2)
## response categories 2 and 3 are collapsed
```

equate

performs Stocking-Lord Equating

Description

Computes linear transformation constants to equate a set of GRM/2PL item parameters to a target scale using a common-item test characteristic curve equating procedure (Stocking & Lord, 1983)

Usage

```
equate(ipar.to, ipar.from, theta)
```

Arguments

ipar.to	a data frame containing target item parameters in the following order: a, cb1, cb2, ..., cb(ncat-1)
ipar.from	a data frame containing to-be-equated item parameters in the following order: a, cb1, cb2, ..., cb(ncat-1)
theta	a theta grid (quadrature points)

Details

Computes linear transformation constants that equate a set of item parameters (ipar.from) to the scale defined by a target item parameters (ipar.to) by minimizing the squared difference between the test characteristic curves as described in Stocking and Lord (1983). The minimization is performed by the nlminb function (in stats).

Value

returns a vector of two elements $c(A, X)$ where A is a multiplicative constant and K is an additive constant

Note

The item parameters are assumed to be on the theta metric (0,1). The number of category threshold parameters can differ across items.

Author(s)

Seung W. Choi <s-choi@northwestern.edu>

References

Stocking, M. L. & Lord, F. M. (1983). Developing a Common Metric in Item Response Theory. *Applied Psychological Measurement*, 7(2), 201-210.

See Also

[tcc](#)

Examples

```
##ipar.to is a data frame containing "target" item parameters
##ipar.from is a data frame containing "to-be-equated" item parameters
## Not run: AK <- equate(ipar.to,ipar.from)
#AK[1] contains the multiplicative constant
#AK[2] contains the additive constant
```

extract	<i>extracts item parameters</i>
---------	---------------------------------

Description

extracts IRT item parameter estimates from an output returned from ltm:grm

Usage

```
extract(ipar)
```

Arguments

ipar output from the grm function in the ltm package

Details

similar to the coef function in the ltm package

Value

a data frame containing item parameter estimates in the order of a, cb1, cb2,..., cb(maxCat-1).

Author(s)

Seung W. Choi <s-choi@northwestern.edu>

See Also

[lordif](#)

Examples

```
##calib.sparse <- grm(sparse.matrix,constrained=FALSE,IRT.param=TRUE)
## Not run: ipar.sparse <- extract(calib.sparse)
```

getcutoff

determines a cutoff threshold

Description

Determines cutoff thresholds for statistics generated from Monte Carlo simulations

Usage

```
getcutoff(stat, alpha, reverse)
```

Arguments

stat	a vector containing statistics sampled from a Monte Carlo simulation
alpha	a value determining the proportion to be cut off from the bottom (or top) of stat
reverse	if TRUE it cuts off the right tail

Details

if reversed is TRUE it cuts off the right tail (i.e., largest values)

Value

returns a scalar that cuts off the designated proportion (specified by alpha)

Author(s)

Seung W. Choi <s-choi@northwestern.edu>

See Also

[montecarlo](#)

Examples

```
#top 1 percent
getcutoff(runif(1000),0.01,TRUE)
#bottom 1 percent
getcutoff(runif(1000),0.01,FALSE)
```

lordif	<i>performs LOGistic Regression Differential Item Functioning using IRT</i>
--------	---

Description

performs iterative hybrid ordinal logistic regression/IRT DIF

Usage

```
lordif(resp.data, group, selection = NULL,
       criterion = c("Chisqr", "R2", "Beta"),
       pseudo.R2 = c("McFadden", "Nagelkerke", "CoxSnell"), alpha = 0.01,
       beta.change = 0.1, R2.change = 0.02, maxIter = 10, minCell = 5,
       minTheta = -4, maxTheta = 4, inc = 0.1, control = list())
```

Arguments

resp.data	data frame or matrix containing item responses
group	a vector of group designations
selection	vector specifying a subset of items to be analyzed or NULL for all items
criterion	criterion for flagging (i.e., "Chisqr", "R2", or "Beta")
pseudo.R2	pseudo R-squared measure (i.e., "McFadden", "Nagelkerke", or "CoxSnell")
alpha	significance level for Chi-squared criterion
beta.change	proportionate change for Beta criterion
R2.change	R-squared change for pseudo R-squared criterion
maxIter	maximum number of iterations for purification
minCell	minimum cell frequency to avoid collapsing
minTheta	minimum for theta grid
maxTheta	maximum for theta grid
inc	increment for theta grid
control	a list of control variables (refer to the grm function in the ltm package)

Details

Performs a ordinal (common odds-ratio) logistic regression DIF analysis using IRT theta estimates as the conditioning variable. The graded response (GR) model is used for IRT trait estimation. Flagged items are treated as separate items and group-specific item parameters are obtained. The procedure runs iteratively until the same set of items is flagged over two iterations.

Value

Returns a list of class "lordif" with the following components:

call	calling expression
options	options used for the run
selection	all or a subset of items analyzed
stats	matrix containing output statistics
flag	logical vector of final flags indicating whether each item is displaying DIF or not
recoded	data frame containing recoded item responses
group	vector of group designation values
ng	scalar for the number of groups
ncat	vector of the number of response categories after collapsing/recoding
calib	vector of theta estimates based on the overall (non-group-specific) item parameters
calib.sparse	vector of theta estimates based on the group-specific item parameters (for DIF items)
iteration	scalar for the number of iterations
ipar	data frame of the overall (non-group-specific) item parameter estimates
ipar.sparse	data frame of the group-specific item parameter estimates
stats.raw	matrix containing output statistics (the same components as stats above but based on raw scores)
meanraw	vector containing mean raw scores
flag.raw	logical vector of DIF final flags based on raw scores

Note

requires the **ltm** and **rms** packages

Author(s)

Seung W. Choi <s-choi@northwestern.edu>

References

- Choi, S. W., Gibbons, L. E., Crane, P. K. (2011). lordif: An R Package for Detecting Differential Item Functioning Using Iterative Hybrid Ordinal Logistic Regression/Item Response Theory and Monte Carlo Simulations. *Journal of Statistical Software*, 39(8), 1-30. URL <http://www.jstatsoft.org/v39/i08/>.
- Crane, P. K., Gibbons, L. E., Jolley, L., and van Belle, G. (2006). Differential item functioning analysis with ordinal logistic regression techniques: DIF detect and difwithpar. *Medical Care*, 44(11 Suppl 3), S115-S123.

See Also

[rundif](#)

Examples

```
## Not run: data(Anxiety)
## Not run: resp.data <- Anxiety[paste("R",1:29,sep="")]
## Not run: age <- Anxiety$age
## Not run: age.DIF <- lordif(resp.data,age,control=list(iter.qN=100,GHk=61,method="SANN"))
## Not run: print(age.DIF)
```

montecarlo

performs Monte Carlo simulations for empirical cutoff thresholds

Description

performs Monte Carlo simulations under no-DIF conditions to generate empirical cutoff thresholds

Usage

```
montecarlo(obj, alpha = 0.01, nr = 100)
```

Arguments

obj	an object returned from lordif
alpha	desired significance level (e.g., .01)
nr	number of replications

Details

Simulated datasets are generated under no-DIF conditions and have the same dimensions as the empirical dataset. Group differences (impact) in theta estimates are preserved in the simulated datasets. Returns empirical thresholds for various statistics and effect size measures.

Value

Returns a list of class "lordif.MC" with the following components:

call	calling expression
chi12	prob associated with the LR Chi-square test comparing Model 1 vs. 2
chi13	prob associated with the LR Chi-square test comparing Model 1 vs. 3
chi23	prob associated with the LR Chi-square test comparing Model 2 vs. 3
pseudo12.CoxSnell	Cox & Snell pseudo R-square change from Model 1 to 2
pseudo13.CoxSnell	Cox & Snell pseudo R-square change from Model 1 to 3
pseudo23.CoxSnell	Cox & Snell pseudo R-square change from Model 2 to 3
pseudo12.Nagelkerke	Nagelkerke pseudo R-square change from Model 1 to 2

```

pseudo13.Nagelkerke      Nagelkerke pseudo R-square change from Model 1 to 3
pseudo23.Nagelkerke      Nagelkerke pseudo R-square change from Model 2 to 3
pseudo12.McFadden        McFadden pseudo R-square change from Model 1 to 2
pseudo13.McFadden        McFadden pseudo R-square change from Model 1 to 3
pseudo23.McFadden        McFadden pseudo R-square change from Model 2 to 3

beta12                   proportional beta change from Model 1 to 2
alpha                    significance level
nr                       number of replications
cutoff                   thresholds for the statistics

```

Note

nr must be a large integer (e.g., 500) for smooth distributions.

Author(s)

Seung W. Choi <s-choi@northwestern.edu>

References

Choi, S. W., Gibbons, L. E., Crane, P. K. (2011). lordif: An R Package for Detecting Differential Item Functioning Using Iterative Hybrid Ordinal Logistic Regression/Item Response Theory and Monte Carlo Simulations. *Journal of Statistical Software*, 39(8), 1-30. URL <http://www.jstatsoft.org/v39/i08/>.

See Also

[lordif](#)

Examples

```

##load PROMIS Anxiety sample data (n=766)
## Not run: data(Anxiety)
##age : 0=younger than 65 or 1=65 or older
##run age-related DIF on all 29 items (takes about a minute)
## Not run: age.DIF <- lordif(Anxiety[paste("R",1:29,sep="")],Anxiety$age)
##the following takes several minutes
## Not run: age.DIF.MC <- montecarlo(age.DIF,alpha=0.01,nr=100)

```

permut *performs permutation test for empirical cutoff thresholds*

Description

performs permutation tests under no-DIF conditions to generate empirical cutoff thresholds

Usage

```
permut(obj, alpha = 0.01, nr = 100)
```

Arguments

obj	an object returned from lordif
alpha	desired significance level (e.g., .01)
nr	number of replications

Details

The vector of group designations is randomly shuffled nr times to estimate the sampling distribution of the statistics when the null hypothesis is true. Returns empirical thresholds for various statistics and effect size measures.

Value

Returns a list of class "lordif.MC" with the following components:

call	calling expression
chi12	prob associated with the LR Chi-square test comparing Model 1 vs. 2
chi13	prob associated with the LR Chi-square test comparing Model 1 vs. 3
chi23	prob associated with the LR Chi-square test comparing Model 2 vs. 3
pseudo12.CoxSnell	Cox & Snell pseudo R-square change from Model 1 to 2
pseudo13.CoxSnell	Cox & Snell pseudo R-square change from Model 1 to 3
pseudo23.CoxSnell	Cox & Snell pseudo R-square change from Model 2 to 3
pseudo12.Nagelkerke	Nagelkerke pseudo R-square change from Model 1 to 2
pseudo13.Nagelkerke	Nagelkerke pseudo R-square change from Model 1 to 3
pseudo23.Nagelkerke	Nagelkerke pseudo R-square change from Model 2 to 3
pseudo12.McFadden	McFadden pseudo R-square change from Model 1 to 2

```

pseudo13.McFadden      McFadden pseudo R-square change from Model 1 to 3
pseudo23.McFadden      McFadden pseudo R-square change from Model 2 to 3
beta12                 proportional beta change from Model 1 to 2
alpha                 significance level
nr                    number of replications
cutoff                thresholds for the statistics

```

Note

nr must be a large integer (e.g., 500) for smooth distributions.

Author(s)

Seung W. Choi <s-choi@northwestern.edu>

References

Choi, S. W., Gibbons, L. E., Crane, P. K. (2011). lordif: An R Package for Detecting Differential Item Functioning Using Iterative Hybrid Ordinal Logistic Regression/Item Response Theory and Monte Carlo Simulations. *Journal of Statistical Software*, 39(8), 1-30. URL <http://www.jstatsoft.org/v39/i08/>.

See Also

[lordif](#)

Examples

```

##load PROMIS Anxiety sample data (n=766)
## Not run: data(Anxiety)
##age : 0=younger than 65 or 1=65 or older
##run age-related DIF on all 29 items (takes about a minute)
## Not run: age.DIF <- lordif(Anxiety[paste("R",1:29,sep="")],Anxiety$age)
##the following takes several minutes
## Not run: age.DIF.MC <- permute(age.DIF,alpha=0.01,nr=100)

```

plot.lordif

Plot method for lordif class

Description

plots diagnostic graphs for items identified as displaying DIF

Usage

```

## S3 method for class 'lordif'
plot(x, labels = c("Reference", "Focal"), ...)

```

Arguments

x	output from lordif
labels	labels for group levels, e.g., c("Male","Female")
...	extra graphical parameters

Details

Generates the following graphs IF there is one or more DIF items: 1. Trait Distributions - density graphs for groups 2. Item True Score Functions - true score functions by theta for groups 3. Differences in Item True Score Functions - unsigned differences 4. Item Response Functions - item response function for groups 5. Impact (Weighted by Density) - unsigned differences weighted by theta distributions for the focal group 6. Comparison of TCCs by group based on all items and DIF items 7. Impact on Theta Estimates - theta estimates by group before and after accounting for DIF

Graphs 2-5 are generated for each DIF item Graphs 1, 6 and 7 are generated for the whole analysis

Note

Produces graphs only if x contains DIF items.

Author(s)

Seung W. Choi <s-choi@northwestern.edu>

See Also

[lordif](#)

Examples

```
##run lordif first
## Not run: age.dif <- lordif(Anxiety[paste("R",1:29,sep="")],Anxiety$age)
## Not run: plot(age.dif,labels=c("Younger","Older"),cex=0.8,lwd=1)
```

plot.lordif.MC

Plot method for Monte Carlo simulation output

Description

Produces plots for Monte Carlo output

Usage

```
## S3 method for class 'lordif.MC'
plot(x, mfrow = c(3, 1), ...)
```

Arguments

x an object of class lordif.MC returned from montecarlo
mfrow number of rows and columns per page for multi-fane plots
... extra graphical parameters

Details

Generates the following graphs: 1. thresholds for Chi-square probability for Model 1 vs. 2 2. thresholds for Chi-square probability for Model 1 vs. 3 3. thresholds for Chi-square probability for Model 2 vs. 3 4. pseudo R-square change from Model 1 to 2 5. pseudo R-square change from Model 1 to 3 6. pseudo R-square change from Model 2 to 3 7. proportional beta change from Model 1 to 2

Value

Returns no object.

Note

x is an object of class lordif.MC returned from montecarlo

Author(s)

Seung W. Choi <s-choi@northwestern.edu>

See Also

[lordif](#)

Examples

```
## s3 plot method for class 'lordif.MC':
## Not run: age.dif <- lordif(Anxiety[paste("R",1:29,sep="")],Anxiety$age)
## Not run: age.dif.MC <- montecarlo(age.dif,alpha=.05,nr=500)
## Not run: plot(age.dif.MC,mfrow=c(1,1))
```

probgrm

calculates item response probabilities

Description

Calculates a matrix of item response probabilities over a grid of theta values for an item

Usage

```
probgrm(theta, a, cb)
```

Arguments

theta	a vector of theta values (e.g., quadrature points)
a	a slope parameter value
cb	a vector of category threshold values

Details

Graded Response Model (Samejima, 1969) is assumed.

Value

Returns a matrix of item response probabilities. The first dimension corresponds to the length of theta.

Author(s)

Seung W. Choi <s-choi@northwestern.edu>

References

Samejima, F. (1969). Estimation of latent ability using a response pattern of graded scores. *Psychometrika Monograph*, 17.

See Also

[calcprob](#)

Examples

```
##
probrm(seq(-4,4,.1), 1.5, c(-1.2,0.5,1.5))
```

recode	<i>recodes item responses</i>
--------	-------------------------------

Description

Recodes item responses as specified by original and modified

Usage

```
recode(vec, original, modified)
```

Arguments

vec	a vector of item responses to be recoded
original	original item response categories, e.g., c(0,1,2,3)
modified	modified item response categories, e.g., c(1,2,3,4)

Details

vec, original, and modified must be of the same mode. original and modified must be of the same length.

Value

Returns a vector of the same length and mode as vec with recoded values.

Author(s)

Seung W. Choi <s-choi@northwestern.edu>

Examples

```
x <- c(0,1,2,3,4,0,1,2,3,4)
y <- c(0,1,2,3,4)
z <- c(1,2,3,4,5)
recode(x,y,z)
##returns c(1,2,3,4,5,1,2,3,4,5)
```

rundif

runs ordinal logistic regression DIF

Description

Runs ordinal logistic regression DIF

Usage

```
rundif(item, resp, theta, gr, criterion, alpha, beta.change,
       pseudo.R2, R2.change)
```

Arguments

item	a selection of items to be analyzed
resp	a data frame containing item responses
theta	a conditioning (matching) variable
gr	a vector of group identifiers
criterion	criterion for flagging (i.e., "CHISQR", "R2", or "BETA")
alpha	significance level for Chi-squared criterion
beta.change	proportional change for Beta criterion
pseudo.R2	pseudo R-squared measure (i.e., "McFadden", "Nagelkerke", or "CoxSnell")
R2.change	R-squared change for pseudo R-squared criterion

Details

The argument item lists the column numbers of the data frame resp to be included in the analysis.

Value

Returns a list of the following components:

stats	a data frame containing output statistics
flag	a logical vector of DIF flags

Author(s)

Seung W. Choi <s-choi@northwestern.edu>

References

Choi, S. W., Gibbons, L. E., Crane, P. K. (2011). lordif: An R Package for Detecting Differential Item Functioning Using Iterative Hybrid Ordinal Logistic Regression/Item Response Theory and Monte Carlo Simulations. *Journal of Statistical Software*, 39(8), 1-30. URL <http://www.jstatsoft.org/v39/i08/>.

Crane, P. K., Gibbons, L. E., Jolley, L., and van Belle, G. (2006). Differential item functioning analysis with ordinal logistic regression techniques: DIF detect and difwithpar. *Medical Care*, 44(11 Suppl 3), S115-S123.

See Also

[runolr](#), [lordif](#)

Examples

```
##
## Not run: rundif(item, resp, theta, gr)
```

runolr	<i>runs ordinal logistic regression models</i>
--------	--

Description

Runs ordinal logistic regression models and produces DIF statistics and effect size measures

Usage

```
runolr(rv, ev, gr)
```

Arguments

rv	a response variable
ev	an explanatory variable (e.g., conditioning variable)
gr	a vector of group identifiers

Details

Model 1: ev Model 2: ev + gr Model 3: ev*gr or equivalently ev + gr + ev*gr

Value

Returns a list of the following components:

chi12	prob for the LR Chi-square comparing Model 1 vs. Model 2
chi13	prob for the LR Chi-square comparing Model 1 vs. Model 3
chi23	prob for the LR Chi-square comparing Model 2 vs. Model 3
beta12	proportional change in the coefficient for ev
pseudo1.CoxSnell	Cox & Snell pseudo R-square for Model 1
pseudo2.CoxSnell	Cox & Snell pseudo R-square for Model 2
pseudo3.CoxSnell	Cox & Snell pseudo R-square for Model 3
pseudo1.Nagelkerke	Nagelkerke pseudo R-square for Model 1
pseudo2.Nagelkerke	Nagelkerke pseudo R-square for Model 2
pseudo3.Nagelkerke	Nagelkerke pseudo R-square for Model 3
pseudo1.McFadden	McFadden pseudo R-square for Model 1
pseudo2.McFadden	McFadden pseudo R-square for Model 2
pseudo3.McFadden	McFadden pseudo R-square for Model 3
pseudo12.CoxSnell	Cox & Snell R-square change from Model 1 to Model 2
pseudo13.CoxSnell	Cox & Snell R-square change from Model 1 to Model 3
pseudo23.CoxSnell	Cox & Snell R-square change from Model 2 to Model 3
pseudo12.Nagelkerke	Nagelkerke R-square change from Model 1 to Model 2
pseudo13.Nagelkerke	Nagelkerke R-square change from Model 1 to Model 3
pseudo23.Nagelkerke	Nagelkerke R-square change from Model 2 to Model 3
pseudo12.McFadden	McFadden R-square change from Model 1 to Model 2

```

pseudo13.McFadden
      McFadden R-square change from Model 1 to Model 3
pseudo23.McFadden
      McFadden R-square change from Model 2 to Model 3
df12
      df for the LR Chi-square comparing Model 1 and Model 2
df13
      df for the LR Chi-square comparing Model 1 and Model 3
df23
      df for the LR Chi-square comparing Model 2 and Model 3

```

Author(s)

Seung W. Choi <s-choi@northwestern.edu>

References

Choi, S. W., Gibbons, L. E., Crane, P. K. (2011). lordif: An R Package for Detecting Differential Item Functioning Using Iterative Hybrid Ordinal Logistic Regression/Item Response Theory and Monte Carlo Simulations. *Journal of Statistical Software*, 39(8), 1-30. URL <http://www.jstatsoft.org/v39/i08/>.

Crane, P. K., Gibbons, L. E., Jolley, L., & van Belle, G. (2006). Differential item functioning analysis with ordinal logistic regression techniques: DIF detect and difwithpar. *Medical Care*, 44(11 Suppl 3), S115-S123.

See Also

[rundif](#), [lordif](#)

Examples

```
##
## Not run: runolr(rv, ev, gr)
```

separate *splits item response vectors of DIF items by group*

Description

Splits item response vectors of DIF items into separate group-specific vectors.

Usage

```
separate(resp, flag, gr)
```

Arguments

```

resp          a data frame (or matrix) of item response vectors
flag         a vector of DIF flags
gr           a vector of group identifiers

```

Details

To obtain group specific item calibrations, response vectors of DIF items are split into multiple vectors by group and treated as separate items.

Value

Returns a data frame with item response vectors for non-DIF items followed by separated item response vectors for DIF items

Author(s)

Seung W. Choi <s-choi@northwestern.edu>

See Also

[lordif](#)

Examples

```
##
## Not run: separate(resp, flag, gr)
```

tcc	<i>computes a test characteristic curve (tcc)</i>
-----	---

Description

computes a test characteristic curve (tcc) from input item parameters

Usage

```
tcc(a, cb, theta)
```

Arguments

a	a vector of slope parameters
cb	a matrix of category boundary/threshold parameters
theta	a grid of theta values

Details

The graded response model is assumed. The lowest score for each item is set to 0 not 1. length(a) must be the same as nrow(cb)

Value

Returns a vector representing a tcc

Author(s)

Seung W. Choi <s-choi@northwestern.edu>

References

Samejima, F. (1969). Estimation of latent ability using a response pattern of graded scores. *Psychometrika Monograph*, 17.

See Also

[equate](#), [probgrm](#)

Examples

```
##  
## Not run: tcc(a,cb,theta)
```

Index

*Topic **datasets**

Anxiety, [3](#)

*Topic **package**

lordif-package, [2](#)

Anxiety, [3](#)

calcprob, [5](#), [7](#), [19](#)

calctheta, [6](#)

collapse, [7](#)

equate, [8](#), [25](#)

extract, [9](#)

getcutoff, [10](#)

lordif, [2](#), [10](#), [11](#), [14](#), [16–18](#), [21](#), [23](#), [24](#)

lordif-package, [2](#)

ltm, [3](#)

montecarlo, [2](#), [10](#), [13](#)

permute, [15](#)

plot.lordif, [16](#)

plot.lordif.MC, [17](#)

probgrm, [6](#), [7](#), [18](#), [25](#)

recode, [8](#), [19](#)

rms, [3](#)

rundif, [12](#), [20](#), [23](#)

runolr, [21](#), [21](#)

separate, [23](#)

tcc, [9](#), [24](#)